

The Wyeth-Scott Company

ESTABLISHED 1906

MANUFACTURER OF THE MORE POWER PULLER®

SAFETY INSTRUCTIONS

For optimal, safe performance, follow all enclosed instructions. Always use the safety handle included with your puller.



Phone 800/743-4521 or 740/345-4528 • Email: sales@wyeth-scott.com • Hours: Mon-Fri 8:30 am - 5:00 pm EST

THIS PULLER ABSOLUTELY MUST BE KEPT GREASED!

DIRECTIONS:

- Use a grease gun with small tip or a Push 'n Lube grease gun. Lithium grease in an aerosol can with straw may be substituted.
- 9/64" grease holes are drilled in important places of the puller for your convenience. See illustration at right.
- Older pullers: if it does not have grease holes drilled, you will need to grease around these same areas.

CRITICAL SPOT TO GREASE! P16 - where yoke P16 attaches to frame. SLT(option) – all P15 - Clevis Pin found in the Holes drilled on safety latch springs and center of the sheave of the both arms of yoke. screws. tackle block book. **R17** P9 – rivets that attach the pawls **CRITICAL SPOT TO GREASE!** should be greased P8 - tubular rivet is from the SLT(option) - all greased from a hole underside. safety latch springs drilled in the center of and screws. R17 reel hub.

REVISED 04.15 © 2015 Wyeth-Scott Company